



**TT250/TT500
TACK DISTRIBUTOR**

POWERTRAIN

5.5 hp Honda engine
Electric engine start option
15 gpm direct-drive asphalt pump with integral relief valve

TACK TANK

250 or 500 gallon capacity
300,000 btu burner
20 lb dual propane tanks
Push button igniter
Fluid level indicator
Tack temperature gauge
DOT 406 emergency venting relief valve
Optional electric tank heater w/ adjustable temperature control

MATERIAL DELIVERY

50' hose reel with 5'6" spray wand
Optional rear-mounted spray bar, adjustable between 6' and 9'
Ball valves allow individual control of 7 spray bar nozzles
Optional wireless spray bar control remote
Tank recirculation valve
Numbered valves for simplified operation
13-gal flush tank for cleaning solvent

TRAILER

4000 lb GVWR trailer for TT250
7200 lb GVWR trailer for TT500
Ball or pintle hitch equipped
Electric brakes
Emergency break-away brake system
Safety tow chains
Pre-wired with a 6-pin connector



OPTIONAL EQUIPMENT

Ball or Pintle Hitch
Spare Tire and Mount
Spray Bar with Manual Valve
Remote from Spray Bar
Electric Start
Electric Tank Heat

WARRANTY

12 months

SALES AND SERVICE

Sold and serviced exclusively through Cat® dealers worldwide

SPECS

Tank Capacity: 250 gal/500 gal
Shipping Weight: 1,850 lb/2,900 lb
Working Weight: 4,000 lb/7,200 lb
Length: 120"/168"
Width: 78"
Height: 80"/86"
Burner: 1 x 300,000 btu
Temperature Gauge: 0 - 250° F
Engine: Honda
Horsepower: 5.5
Pump: 15 gpm direct drive
Spray Wand: 5'6" single nozzle
Spray Bar: 6' to 9', 7 nozzles
Hose Reel: 50 ft
Flush Tank: 13 gal

