



POWERTRAIN

Cat® C3.4 Tier 4 engine, 100 hp (74 kW)
3-Speed hydrostatic drive, 350 fpm (106 mpm) transport speed
Automatic track tensioning
90" (2,286 mm) track length
68" (1,727 mm) of ground contact
14" (355 mm) performance, poly track pads
6 track rollers per side
140mm track chain pitch
Hydraulically driven 12 kW generator

OPERATING ENVIRONMENT

Dual operating stations
3 operating positions - high, mid and screed
Push button keypads
LCD display provides conditions and diagnostics
Pause mode enables return to same settings
Steering wheel standard, joysticks optional

MATERIAL DELIVERY

9-ton (8.1 mt) hopper
Replaceable floor plates
Heavy-duty chains and flight bars
Narrow chain guards
12" (305 mm) Ni-hard augers
Adjustable push roller
Independent auger and conveyor control
Cut-off doors
Independent hopper control

SCREED

8' (2.4 m) to 15'8" (4.7 m) standard paving width
4 element electric heated screed w/ thermostatic control
3/8" (9.5 mm) thick screed plates
Grade and slope controls
Sonic feed sensors
Manual crown adjustment (+-3%)
Folding rear walkway
Adjustable end gates
Replaceable wear plates
2,500 vpm vibrator

SERVICE

10-gal. (37 L) washdown system with 2 hoses/nozzles
Braided electrical harnesses and sealed connections
Color-coded electrical wires
12-volt electric system with automotive-type fuses
Remote grease fittings
5 engine access doors
Lockable vandal covers and engine access doors



OPTIONAL EQUIPMENT

Truck Hitch Group
Hydraulically Extendable Push Rollers
Additional Operators Seat Group
Walk Way Extension Group
Joystick Control Group
LED Strobe Light Group
Work Lights Group
Premium LED Work Lights Group
Screed Mounted Control Panels
Hand Held Remote Group
TOPCON P-32 Grade and Slope Controls
MOBA-MATIC II Grade and Slope Controls
Heated End Gates
Electric Screed Extension Height Adjustment
Power Hydraulic Slope
Hydraulic Power Crown
Cut-Off Shoe Group

WARRANTY

12 months standard
Extended warranty available

SALES AND SERVICE

Sold and serviced exclusively through Cat dealers worldwide

SPECS

Weight:	19,500 lb	8,845 kg
Length:	14'5"	4,394 mm
Width:	101"	2,565 mm
Height:	76"	1,930 mm
Truck Clearance:	19"	482 mm
Auger Diameter:	12"	305 mm
Auger Speed:	150 rpm	
Fuel Tank Capacity:	34 gal	128 L
Hydraulic Tank Capacity:	34 gal	128 L
DEF Tank Capacity:	5 gal	18 L
Paving Speed:	150 fpm	45 mpm
Transport Speed:	350 fpm	106 mpm
Screed Weight:	3,000 lb	1,360 kg
Main Plate Width:	16.5"	419 mm
Plate Extension Width:	9"	228 mm
Vibration:	2 x 2,500 vpm	



UNMATCHED PRODUCTIVITY

- Compact balanced weight of 19,500 lb (8,845 kg) allows for easy transport
- Independent control of the left and right side of the feeder system enables variable width paving
- Pause mode maintains settings for easy restarts
- Heavy duty conveyor slats efficiently provide material to the screed
- Best in class, 9 (8.1 mt) ton hopper capacity
- Cat® C3.4 Tier 4 engine with 100 hp (74 kW) provides clean, quiet power and no lost time during regeneration cycle



PROVEN SCREED

- Hydraulically extendable paving range of 8' (2.4 m) to 15'8" (4.7 m)
- Heaviest in class 3,000 lb (1,360 kg) screed for exceptional mat quality
- Cutoff doors provide a paving range of 0 to 3'10" (1,168 mm)
- Electric screed heat eliminates propane tank and fumes
- Fold-able rear walkway with optional sliding extensions optimize visibility
- Extender height adjusters match main screed height
- Angle of attack adjusters on main screed and extensions
- Grade and slope control option for automatic height control



DURABLE LONG-LIFE COMPONENTS

- Best in class track length of 90" (2,286 mm)
- Automatic track tensioning maximize component life
- 14" (355 mm) poly pads deliver traction, stability and long-life performance
- Best in class chain pitch of 140mm delivers maximum track life
- Highway class conveyor chains with tool-less adjustment
- Highway class conveyor and auger bearings with remote grease lines
- Largest in class hydraulic-driven, thermostatically controlled cooling package for quiet performance



EXCELLENT VISIBILITY AND CONTROL

- 3 different operating positions, top, mid-level and screed optimize visibility and meet crew requirements
- Magnetic resistance steering wheel provides reliable control
- Screed mounted control panel offers more function controls for operators
- Optional remote for tow-point, extender width and feeder system override
- Individual cut-off doors prevent spillage and limit cleanup and automatically close when reversing direction



SERVICE AND SUPPORT

- Cat® Dealer sales, service and support
- Electronic controller provides diagnostic capability
- Manual overrides on hydraulics ensure jobs are completed
- Visual indicators for routine maintenance checks
- Weiler trained dealer service technicians
- Product and application assistance from certified paving specialists
- Readily available off-the-shelf OEM parts that meet precise specifications